



SERIE	TAMAÑO	CAUDAL	ALTURA	PRESION	CONSUMO AIRE	RANGO PRESION DE AIRE
TC-X030	NPT 1/4"	2.1 GPM (8.0 LPM)	230 FT (70 M)	100 PSI (7 bar)	8.83 scfm (250 L/min)	30-100 PSI (2 - 7 bar)
TC-X050	NPT 1/4"	3.0 GPM (11.5 LPM)	230 FT (70 m)	100 PSI (7 bar)	8.83 scfm (250 L/min)	30-100 PSI (2 - 7.0 bar)
TC-X100	NPT 3/8"	4.8 GPM (18 LPM)	230 ft (70 m)	100 PSI (7 bar)	8.83 scfm (250 L/min)	30-100 PSI (2 - 7 bar)
TC-X101	NPT 3/8"	6.1 GPM (23 LPM)	230 ft (70 m)	100 PSI (7 bar)	10.6 scfm (300 L/min)	30-100 PSI (2 - 7 bar)
TC-X102	NPT 3/8"	6.3 GPM (24 LPM)	230 ft (70 m)	100 PSI (7 bar)	14.1 scfm (400 L/min)	30-100 PSI (2 - 7 bar)
TC-X150	NPT 1/2"	7.4 GPM (28 LPM)	230 ft (70 m)	100 PSI (7 bar)	10.6 scfm (300 L/min)	30-100 PSI (2 - 7 bar)
TC-X151	NPT 1/2"	14.3 GPM (54 LPM)	230 ft (70 m)	100 PSI (7 bar)	15.9 scfm (450 L/min)	30-100 PSI (2 - 7 bar)
TC-X152	NPT 1/2"	15.8 GPM (60 LPM)	230 ft (70 m)	100 PSI (7 bar)	31.8 scfm (900 L/min)	30-100 PSI (2 - 7 bar)
TC-X202	NPT 3/4", ANSI 150 lb 3/4"	31.7 GPM (120 LPM)	230 ft (70 m)	100 PSI (7 bar)	42.4 scfm (1200 L/min)	30-100 PSI (2 - 7 bar)
TC-X252	NPT 1", ANSI 150 lb 1"	43.6 GPM (165 LPM)	230 ft (70 m)	100 PSI (7 bar)	56.5 scfm (1600 L/min)	30-100 PSI (0 - 7 bar)
TC-X253	NPT 1"	58.1 GPM (220 LPM)	230 ft (70 m)	100 PSI (7 bar)	70.6 cfm (2000 L/min)	30-100 PSI (2 - 7 bar)
TC-X400	NPT 1 1/2", ANSI 150 lb 1 1/2"	100.4 GPM (380 LPM)	230 ft (70 m)	100 PSI (7 bar)	106 cfm (3000 L/min)	14-100 PSI (1 - 7 bar)
TC-X401	NPT 1 1/2", ANSI 150 lb 1 1/2"	158.5 GPM (600 LPM)	280 ft (85 m)	125 PSI (8.5 bar)	117.3 cfm (6000 L/min)	30-125 PSI (1 - 7 bar)
TC-X500	NPT 2", ANSI 150 lb 2"	190.2 GPM (720 LPM)	280 FT. (85m)	125 PSI (8.5 bar)	212 scfm (6000 L/min)	30-125 PSI (1 - 7 bar)
TC-x800	NPT 3", ANSI 150 lb 3"	211.3 GPM (800 LPM)	280 FT. (85m)	125 PSI (8.5 bar)	230 scfm (6500 L/min)	14-125 PSI (1 - 7 bar)